

Listing of Claims:

1. (currently amended) A skimmer and filter unit for use with a body of water, comprising:
 - a tank portion receiving water from a body of water;
 - a skimmer chamber within said tank portion; and
 - an ultraviolet light chamber within said same tank portion.
2. (original) The skimmer and filter unit of claim 1 further comprising a pump chamber within said tank.
3. (original) The skimmer and filter unit of claim 1 further comprising a filter chamber within said tank portion.
4. (original) The skimmer and filter unit of claim 1 wherein said tank portion comprises:
 - an upright approximately cylindrical tank; and
 - a neck extending from said tank, said neck comprising a weir faceplate assembly.
5. (original) The skimmer and filter unit of claim 4 wherein said weir faceplate assembly comprises:
 - an interchangeable weir faceplate defining a weir opening;
 - a pivoting weir door
 - a weir divider slidable into mating slots of said neck to form a fluid conduit that coincides with the dimensions of said weir opening.
6. (original) The skimmer and filter unit of claim 4 wherein said weir faceplate assembly comprises a locking tab for securing a weir door in a closed position

7. (original) The skimmer and filter unit of claim 1 further comprising an interlocking lid mating to said tank portion for reducing deformation of said tank portion by an environment.

8. (original) The skimmer and filter unit of claim 7 wherein said lid comprises a coarse exterior surface for increased frictional contact with external surroundings.

9. (original) The skimmer and filter unit of claim 1 wherein said ultraviolet light chamber comprises an interior and exterior defined by said tank portion, said interior for containing an ultraviolet light, said exterior for receiving a mount, said mount comprising mating slots for receiving a locking ring affixed to said ultraviolet light.

10. (original) The skimmer and filter unit of claim 1 wherein said ultraviolet light chamber is in fluid communication with said skimmer chamber.

11. (original) The skimmer and filter unit of claim 2 further comprising a bypass valve positioned between said pump chamber and said skimmer chamber.

12. (original) The skimmer and filter unit of claim 3 wherein said ultraviolet light chamber is in fluid communication with said filter chamber.

13. (original) The skimmer and filter unit of claim 3 further comprising a pump chamber, said pump chamber in fluid communication with said filter chamber.

14. (currently amended) A method of treating water from a body of water, the method of comprising the steps of:

receiving water through a weir opening in a tank;

skimming water received through the weir opening;

subjecting the received water to ultraviolet light within the same tank.

15. (original) The method of claim 14 further of comprising the step of directing the water through a filter chamber.

16. (original) The method of claim 14 further of comprising the step of directing the water from a skimming chamber downward and toward an ultraviolet light chamber.

17. (original) The method of claim 14 further of comprising the steps of:
sensing the water level in a pump chamber; and
operating a bypass valve between a pump chamber and a skimmer chamber based upon the sensed water level.

18. (currently amended) A method of treating water from a body of water, the method of comprising the steps of:
receiving water through a weir opening located at an upper portion of an upright tank;
skimming water with a skimmer basket located downstream and approximately beneath the weir opening;
directing skimmed water through a unidirectional port defined in a lower portion of a partitioning wall of the upright tank to an ultraviolet light chamber within the same tank.